

720i™ Series

Programmable Weight Indicator/Controller



Standard Features

- LCD display size: panel mount (3.8 in x 1.2 in), universal (5.3 in x 1.5 in)
- Four softkeys
- Truck in/out, 1,000-ID memory
- Process control engine ProAction PCE define conditions and actions
- Data storage onboard, ProAction DBE user-defined
- Eight digital I/O (expandable)
- One option slot for pluggable options
- 20 auxiliary print formats
- Time & date
- Audit trail tracking and alibi storage
- Peak hold
- Rate of change
- Accumulator
- Multi-range/interval
- Local/remote
- Two full duplex serial ports
- One PS-2 keyboard port
- Header for fiber optic, Ethernet or USB
- Configurable with Revolution® software

Optional Communication:

- Ethernet TCP/IP
- RS-485 4 wire
- Fiber optic
- USB
- Wi-Fi
- Network Protocols

Approvals



Measurement
Canada
Approved



Panel Mount



CPU Enclosure

Specifications

Power:

Line voltages: 100–240VAC
Frequency: 50-60 Hz
DC voltages: 12–24VDC
Power consumption: 25W

Excitation Voltage:

10VDC, 8 x 350Ω or 16 x 700Ω load cells

Analog Signal Input Range:

-10 mV to +45 mV

Analog Signal Sensitivity:

0.3 μV/graduation minimum at 7.5 Hz
1.0 μV/graduation typical at 120 Hz (manual only)
4.0 μV/graduation typical at 960 Hz (manual only)
1.0 μV/graduation recommended

A/D Sample Rate:

7.5 to 960 Hz, software selectable

Resolution:

Internal: 8 million counts/8,000,000 23 bit
Display: 9,999,999

System Linearity / PI Rating:

±0.01% full scale

Digital I/O:

Eight channels on CPU board; optional 24-channel I/O

Communication Ports:

Two ports on CPU board support up to 115,200 bps
Port 2: Full duplex RS-232 with handshaking
Port 4: Full duplex RS-232, simplex 20mA
Keyboard port hard wired (Scan Code 1)
Optional dual-channel serial expansion boards available
Channel A: RS-232, RS-485, 20 mA
Channel B: RS-232, 20 mA

Display:

Panel Mount: 3.8 in x 1.2 in (96 mm x 30 mm)
Universal: 5.3 in x 1.5 in (133 mm x 39 mm)
240 x 64 pixel, Transflective LCD with adjustable contrast

Keys/Buttons:

Ten-key (panel mount) membrane panel
22-key (universal mount) membrane panel tactile feel
Optional keyboard connection supported

Temperature Range

Certified: 14°F to 104°F (-10°C to 40°C)
Operating: 14°F to 122°F (-10°C to 50°C)

Weight:

Universal enclosure: 9.5 lb (4.3 kg)
Panel Mount enclosure: 8.5 lb (3.9 kg)

Rating/Material:

NEMA Type 4X/IP66, stainless steel

Warranty:

Two-year limited warranty

EMC Immunity:

EN 50082 Part 2 IEC EN 61000-4-2, 3, 4, 5, 6, 8, and 11

Approvals:

NTEP CC 08-022, Class III/IIIL 10,000d
Measurement Canada AM-5677C Class III/IIIRD 10,000d
OIML R76/1992-GB1-10.09 Class III 10,000d
EU Test Certificate GB-1380 Class III 10,000d
CE Marked
UL/cUL Listed (universal)
UL/cUL Recognized (panel mount)

720i™ Series


Programmable Weight Indicator/Controller

Part Number/Price

Part #	Description	Est. Weight	Price
PCE Software			
101230†	720i Universal, 115 VAC	12 lb	Consult
103459††	720i Universal, 115–230VAC, CE/OIML	12 lb	Consult
107708*	720i Universal, 12–24VDC	12 lb	Consult
101229**	720i Panel Mount, 115–230VAC	12 lb	Consult
119116**	720i Panel Mount, 115–230VAC, CE/OIML	12 lb	Consult
107710*	720i Panel Mount, 12–24VDC	12 lb	Consult
Batch Software			
115447†	720i Universal, 115 VAC	12 lb	Consult
115448††	720i Universal, 115–230VAC, CE/OIML	12 lb	Consult
115449**	720i Panel Mount, 115–230VAC	12 lb	Consult


*DC/DC converter installed option, not UL approved

**Power cord sold separately



Options/Accessories

Part #	Description	Price
Option Cards		
67601	Digital I/O, 24-channel	Consult
67602	Analog output: selectable 0-10 V, 0-20 mA	Consult
67604	Serial, dual channel	Consult
93245	USB Port (PC connection only-replaces serial port 2)	Consult
Network Cards		
77142	Ethernet TCP/IP Port (replaces serial port 2)	Consult
71986	Ethernet TCP/IP module (installed in option slot)	Consult
108671	Wireless LAN Card 802.11 A/B (replaces serial port 2)	Consult
87803	EtherNet/IP®	Consult
68539	Remote I/O interface	Consult
68540	Profibus® DP interface	Consult
68541	DeviceNet™ interface	Consult
Hardware		
15436	Power cord for panel mount NEMA Type 5-15 plug	Consult
105382	Power cord for panel mount CEE 7/7 plug	Consult
93359	PS/2 keyboard	Consult
19369	Start/stop switch box	Consult
83570	Clear protective overlay (package of five)	Consult
118975	Panel mount kit, for universal	Consult
101923	Remote relay box, does not include relay	Consult
Manuals & Software		
103121	Installation manual	Consult
104033	720i toolkit CD	Consult
107622	720i ProAction Simulator CD	Consult
Primary Component Parts		
106788	CPU board assembly	Consult
101244	LCD Display (panel mount) transfective	Consult
102888	LCD Display (universal) transfective	Consult
101239	Display board (includes display for panel mount)	Consult
102887	Display board (w/o display for universal)	Consult
67613	AC power supply 100-240 nominal, 25 watt	Consult
132791	DC/DC converter 12-24VDC nominal, 25 watt	Consult
101256	Switch membrane for panel mount	Consult
101257	Switch membrane for universal	Consult




720i Panel Mount Display Dimensions

A	7.36 in (187 mm)	D	2.45 in (62 mm)	G	6.12 in (155 mm)
B	1.60 in (41 mm)	E	3.88 in (99 mm)		
C	0.59 in (15 mm)	F	0.62 in (16 mm)		

720i Panel Mount CPU Enclosure

(L x W x H): 12.75 x 6.05 x 2.14 in (324 x 154 x 5 mm)



720i Universal Dimensions

A	10.50 in (267 mm)	D	0.44 in (11 mm)	G	5.25 in (133 mm)
B	7.25 in (184 mm)	E	3.51 in (89 mm)		
C	9.66 in (245 mm)	F	2.31 in (59 mm)		